

a measurable difference...



Foam Porosity Tester Digital

Model: F0023

The Digital Foam Porosity Tester is an instrument for monitoring the porosity of flexible cellular polyurethane. The machine determines the ease with which air passes through a cellular structure. Airflow values may be used as an indirect measurement of certain cell structure characteristics. A flexible cellular test piece, 50mm x 50mm x 25mm, is placed in a cavity over a vacuum chamber and a specified constant differential air pressure is created. The rate of airflow required to maintain this pressure, is the airflow value.

Application:

- Flexible cellular polyurethane

Features:

- Digital Flow Range: 60-600 L/min
- Digital Manometer: 100-500 Pa
- Variable Flow Range
- Test head area: 50mm x 50mm

Benefits:

- Digital operation
- Quick and simple process
- Useful for Quality Control
- Precise, repeatable tests

Standards:

- AS 2282.14
- ASTM D3574 - Test G
- ISO 7231
- BS EN ISO 7231
- DIN EN ISO 7231
- EN ISO 7231

Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or 110 VAC @ 60 HZ
(please specify when ordering)



Dimensions:

- **H:** 650mm • **W:** 650mm • **D:** 850mm
- **Weight:** 40kg

10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: www.idminstruments.com.au

Email: idm@idminstruments.com.au

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd. All Rights Reserved.