

YARN TENSIOMETER YTM LH-605



CHECKING TENSION?

*Check the Outstanding features of Lawson-Hemphill's YARN TENSIOMETER
For Knitting, Winding, Texturizing, Quilling and other applications!*



TENSIONS... Their importance!

The measurement of yarn tension is extremely important in all textile applications. Tension discrepancies between multiple strands or new spools often result in faulty or ruined end-product.

Its compact size and ease-of use make it ideal for measuring tension in hard-to-reach places that are normally difficult for larger tensiometers to access.

This accurate, hand-held Tensiometer gives the operator freedom to make necessary adjustments to the operation being checked. It is accurate within 2% ($\pm 1/2$ g in the 25g unit).

The YTM is durable as well as very affordable; making it ideal for use in the production environment. Easy to Calibrate, it is available in 0-25g, 0-50g and 0-100g ranges.

ORDERING INFORMATION

YTM-25	0 to 25 gram tensiometer
YTM-50	0 to 50 gram tensiometer
YTM-100	0 to 100 gram tensiometer

**Yarn Tensiometers
Available in 3 ranges
25, 50 and 100 gram**



Contact us today for information on this or any of our products

Please call +1 508 679 5364 or e-mail: information@Lawsonhemphill.com

Please visit our website www.Lawsonhemphill.com

Testing Machines Inc.
40 McCullough Drive
New Castle, Delaware 19720
Tel: +1 302 613 5600
Fax: +1 302 613 5619
Info@testingmachines.com

Büchel BV
t/a Messmer Büchel
Fokkerstrat 24, 3905 KV
Veenendaal, Netherlands
Tel: +31 (0)318 521500
Fax: +31 (0)318 540358

**Lako Tool and
Manufacturing Inc.**
7400 Ponderosa Road
Perrysburg, Ohio 43552
Tel: (419) 662-5256
Fax: (419) 662-8225

Lawson Hemphill
1658 G A R Highway
Swansea, MA 02777
Tel: (508) 679-5364
Fax: (508) 679-5396
Information@Lawsonhemphill.com

Adamel Lhomargy SARL
Z.A. de l'Habitat,
Bâtiment 6
Route d'Ozoir, 77680
Roissy en Brie, France
Tel: +33 (0) 1 6440291
Fax: +33 (0) 1 64409211

TMI Canada
P.O. Box 203
Pointe-Claire Dorval
QC, H9R-4N9 CAN
Tel: (514) 426-5855
Fax: (514) 426-1557