

*a measurable difference...*



## Ring Crush Test Fixture

### Model: R0008

The Ring Crush Test fixture is designed to carry out the ring crush test for paper and board having an average thickness up to 1000µm, for the purpose of MD ring crush, CD ring crush, liner or fair side. The test piece of paper or board is supported in the Ring Crush Holder and subjected to edgewise compression between the platens of a crush testing machine. A branch groove is cut from the edge to permit insertion of the test piece. One of a series of replaceable discs rests in the centre. The discs are of various diameters so that the width of the groove formed between the edge of the disc and the wall of the cylindrical hole may be varied to accommodate test pieces of various thicknesses.



### Application:

- Paper
- Paper board

### Features:

- Cylindrical recess 6.35 +/- 0.25mm deep
- Inside diameter 49.275 +/- 0.025mm

### Standards:

- AS/NZS 1301.407s
- TAPPI T818
- TAPPI T822

### Options:

- Crease & Stiffness Cutter required to cut samples
- Calibration check weights 100gms, 200gms x2

### Dimensions:

- **H:** 140mm
- **W:** 275mm
- **D:** 150mm
- **Weight:** 0.2kg

10-11 Colorado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: [www.idminstruments.com.au](http://www.idminstruments.com.au)

Email: [idm@idminstruments.com.au](mailto:idm@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd. All Rights Reserved.