

*a measurable difference...*

## Vertical Foam Impact Tester

**Model:** V0001

This instrument performs the procedure for determining the dynamic cushioning performance of cellular rubber materials and rigid and flexible cellular plastics, by measuring the peak deceleration of a mass when it is dropped on a test piece. The test described is intended primarily for quality assurance.

### Application:

- Foam packaging materials

### Features:

- Flat-based drop hammer
- Adjustable hammer mass
- Piezo-electric transducer
- Electro-magnet release
- Hand controlled

### Standards:

- AS 2282.11
- ISO 4651

### Options:

- Pendulum apparatus

### Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or  
110 VAC @ 60 HZ

*(please specify when ordering)*

### Dimensions:

- **H:** 2,200mm
- **W:** 320mm
- **D:** 300mm
- **Weight:** 75kg



10-11 Colorado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: [www.idminstruments.com.au](http://www.idminstruments.com.au)

Email: [idm@idminstruments.com.au](mailto:idm@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments reserves the right to make alterations to its product range from time to time.